



Technical Details

ZENITH HI VIZ HELMET

EXTERNAL SHELL: P.P. Polypropylene
 INTERNAL SHELL: HD Expanded polystyrene
 HEADBAND: Soft PA Nylon
 SIZE: Universal-adjustable from 53 to 63 cm
 STANDARD: EN 397 – EN 50365 (Class 0)

 400 g (without accessories)  -30°C / +50°C

SC2 EARMUFFS

Attachment to the helmet with a bayonet adapter
 Universal 30 mm euro slot
 Smooth telescopic size regulation
 Non-conductive
 Certified for use with KASK helmet

 271 g **SNR** >26-30 dB (A)

ZEN MESH VISOR

MATERIAL: Metal
 STANDARD: EN 1731/ANSI Z87.1
 LIGHT TRANSMISSION: 50%

 100 g

 * Protection against side, front and rear impacts in conformity with the requirements of the EN 12492



WHE00026.203
ORANGE



WHE00026.210
BLACK



WHE00026.221
YELLOW FLUO

Zenith Hi Viz Technology



ELECTRIC SHOCK PROTECTION

PROTECTION AGAINST ELECTRIC SHOCK: Helmet provides protection against electrical hazards for use in the vicinity of low voltage systems with voltages up to 1500V DC or 1000V AC.



LUMINESCENT

LUMINESCENT CLIPS: Helmet is equipped with strong external luminescent carrying clips, compatible with all headlamps with elastic bands on the market.



REFLECTIVE

REFLECTING STICKERS: Adhesive reflective stickers for high visibility.



CHINSTRAP EN 397

CHINSTRAP EN 397: Four point chinstrap fixed to the external shell without metal rivets with Quick release fastening and opening in conformity with EN 397. Provided with lateral divider for adjusting the length of the straps.



ECO

ECO LEATHER CHIN PAD: Chin pad with eco-leather chinstrap. The anallergic and washable chinstrap is extremely comfortable and helps to avoid irritation of the skin.



RING TO HOOK

RING TO HOOK: Fitted with a special loop on the chinstrap which allows the helmet to be connected to the harness.



FRONT PAD

REMOVABLE FRONT PAD: Front-end padding easily removable and washable. Developed to guarantee maximum breathability and optimum moisture absorption. Designed to adhere to the front, optimizing comfort.



FAST3DRY

FAST 3DRY: High-tech 3D fabric that dries very quickly, helping the dispersion of moisture to the outside and leaving a pleasant feeling of freshness.



UP&DOWN 2.0

UP & DOWN 2.0: The innovative and exclusive UP & Down 2.0 technology ensures a precise and comfortable fit around the back of the head. The center wheel and the two side wings allow the quick adjustment of the helmet not only in width but also in height and tilt.



VISOR

VISOR ATTACHMENT: Provided with attachment for fitting Zenith visors.



EARMUFFS

EARMUFFS FITTING: Provided with integrated slot for earmuffs with bayonet attachment. Compatible with KASK earmuffs.

SC2 Earmuffs technology

The yellow SC2 earmuffs are suitable for environments with a medium to high level of noise (dB). The best choice in high frequency noise situations. Suitable for a wide variety of uses such as: building and construction, forestry use, industrial areas, production areas, agriculture, ecc.



YELLOW - WHP00005

| SC2 Cap mounted, EN 352-3:2002, Weight 271g, PZT GmbH Notified Body: 1974 | | | | | | | | | | | | |
|---|------|------|------|------|------|------|------|------|----|----|----|-----|
| Frequency Hz | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | H | M | L | SNR |
| Mean Attenuation | 15,0 | 15,0 | 21,0 | 28,1 | 35,3 | 34,0 | 34,0 | 37,3 | | | | |
| Std. dev | 4,1 | 2,6 | 3,1 | 3,5 | 4,0 | 3,8 | 4,5 | 4,4 | 31 | 27 | 19 | 29 |
| APV | 10,9 | 12,4 | 17,9 | 24,6 | 31,3 | 30,2 | 29,5 | 32,9 | | | | |

Zen Mesh Visor technology

The metal visor, consisting in a special hexagonal weave, guarantees higher transparency for major security also in low visibility conditions. The visor protects against dust particles and abrasion and is placed close to the face for superior protection. The inner air flow guarantees an active micro-ventilation and gives a pleasant feeling of comfort. Also ideal for overlapping corrective glasses. Compatible with models: Zenith; Zenith BA, Zenith BA AIR, Zenith PL

Additional Information



GUARANTEE

3 years starting from the purchasing date.

SHELF LIFE

10 years starting from the production date (production date is printed on a label contained on the inside of the helmet). Inspect the helmet regularly to check for any damage! Cuts, abrasions, deformation or changes in colour represent important elements for checking the helmet status.

CLEANING

Clean the helmet only with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). Do not use chemical detergent or solvent.

STORAGE

When not in use the helmet should be stored away from direct sunlight or source of heat.

ADHESIVE APPLICATION

Do not apply adhesives, solvents, stickers or paint that do not comply with the manufacturer's specifications. Any alteration or intervention not provided for may impair its protective function.

Accessories



WV100007
ZEN Visor



WV100008
ZEN FF Visor



WV100009/10
ZEN MM/PM Visor



WV100014
Arc Flash 1



WV100015
Arc Flash 2



WAC00010
ZEN FF, ZEN MM/PM
visor carrier



WAC00009
Adapters for visor



WPA00008
Extra-comfort spacer



WHP00004/5/6
Earmuffs



WAC00013/25
Neck Shade



WPA00007
Winter padding



WAC00026
Helmet bag